



Journal of Urban and Environmental  
Engineering,  
ISSN 1982-3932  
doi: 10.4090/juee.2009.v3n1.001006

**Journal of Urban and  
Environmental Engineering**

[www.journal-uee.org](http://www.journal-uee.org)

## DEVELOPMENT OF MICROBIAL CONSORTIUM FOR THE BIODEGRADATION AND BIODECOLORIZATION OF TEXTILE EFFLUENTS

*Rajendra R1., Hasabo A. Mohammed Ahmed2, Sundaram S. Karthik 1*

*1 PG & Research Department of Microbiology, PSG College of Arts & Science, Coimbatore 14, INDIA*

*2 Africa City of Technology, Khartoum, SUDAN*

### Abstract:

In the current study 3 bacterial species (*Bacillus* sp., *Pseudomonas* sp., and *Alcaligenes* sp.) and 2 fungal species (*Aspergillus* sp., and *Penicillium* sp.) screened from 265 bacterial isolates and 35 fungal isolates respectively, were used in 23 different combinations for the biotreatment of textile waste water collected from Karur, Tiruppur and Coimbatore districts under aerated conditions. The Chemical oxygen demand (COD), Total solids (TS) Total dissolved solids (TDS) & Total suspended solids (TSS), Hardness, and color intensity of the textile effluent was found to be very high than the permissible limits before treatment. After treatment one particular combination was capable of reducing the COD of the effluent sample by 75 %. About 5 combinations of microbes efficiently reduced the color of the effluent by more than 50%. Another combination was found to be the most effective in the reduction of TS and TDS by 90% and 69% respectively. Though there was no drastic change in the pH of the sample it was not of great concern as the pH of the sample was well within the permissible limits for the discharge of the wastewater in to natural sources after treatment.

**Key Words: Microbial Consortium, Biodegradation, Biodecolorization, Textile effluents.**

© 2008 Journal of Urban and Environmental Engineering (JUEE). All rights reserved.

\* Correspondence to: Celso A.G. Santos, Tel.: +55 83 3216 7684 Ext 27; Fax: +55 83 3216 7684 Ext 23.  
E-mail: [celso@ct.ufpb.br](mailto:celso@ct.ufpb.br)

## INTRODUCTION

Our biosphere is under constant threat from continuing environmental pollution. Impact on its atmosphere, hydrosphere and lithosphere by anthropogenic activities on water, air and land have negative influence over biotic and abiotic components on different natural eco-systems. In recent years different approaches have been discussed to tackle man made environmental hazards. Clean technology, eco-mark and green chemistry are some of the most highlighted practices in preventing and or reducing the adverse effect on our surroundings.

Among many engineering disciplines, Textile various chemical processing of textiles, large volumes of wastewater with numerous pollutants are discharged. Since the stream of water affect the aquatic eco-system anaerobic condition, a special attention needs to be demanded.

The control of water pollution has found increasing attention in the recent year by the governments especially after record findings of cancer cases of unidentified causes. A known case where azo dyes were found to be potential carcinogenic in the Cristais River of Brazil close to a textile azo dye processing plant where its effluent is disposed and has impacts on a drinking water of the surrounding area (Lima et al 2007).

The release of dyes into the environment constitutes only a small proportion of water pollution, but dyes are visible in small quantities due to their brilliance.

Coimbatore "The Manchester of South India" is thriving mostly on the wealth generated by the textile industries at large. Though it brings in more investment, more jobs more profit, the processing and dyeing part of the industry brings in more organic content and color to the final effluent which when released to the natural water body creates havoc in the surrounding environment. Without suitable treatment, such wastewater would destroy the natural water environment (Banat et al. 1996). The azo-dyes, including reactive, acid, direct dyes and vat dyes are commonly used in the textile industry. The water consumption and wastewater generation from a textile industry depends upon the processing operations employed during the conversion of fiber to textile fabric. On the basis of waste and wastewater (or effluent) generation, the textile mills can be classified (ISPCH, 1995) into two main groups viz., Dry processing mill and Woven fabric finishing mills. These stages consume approximately 2400 to 2700 m<sup>3</sup>/day of raw water (ISPCH, 1995). The wastewater characteristics depend upon the processing stages. In general, the wastewater from a typical cotton textile industry is characterized by high values of Biological

Engineering has direct connection with environmental aspects to be explicitly and abundantly considered. The main reason is that the textile industry plays an important role in a country like India and it accounts for around one third of total export. Out of various activities in textile industry, chemical processing contributes about 70% of pollution. It is well known that cotton mills consume large volume of water for various processes such as sizing, desizing, scouring, bleaching, mercerization, dyeing, printing, finishing, of and washing.

Due to the nature of dyes and auxiliaries a number of ways such as depleting the dissolved oxygen content or settlement of suspended substances in Oxygen Demand (BOD), Chemical Oxygen Demand (COD), color, and pH (ISPCH, 1995). Because of the high BOD, the untreated textile wastewater can cause rapid depletion of dissolved oxygen if it is directly discharged into the surface water sources causing a great damage to environment. The high color renders the water unfit for use at the downstream of the disposal point. The advanced oxidation processes are costly in terms of installation, operation and maintenance costs. Biological processes are cheaper than the others. Investment costs for biological processes are five to twenty times less than chemical ones such as ozone or hydrogen peroxide and the running costs are three to ten times less. In view of the above adverse effects, the textile industry effluent is to be treated and discharged according to the standards prescribed under Central Water (Prevention and Control of Pollution) Act, 1974.

This work aims to isolate indigenous predominant adapted bacterial and fungal strains from textile effluents which possess the ability to decolorize and degrade a variety of textile effluents. These isolates were used to develop a microbial consortium that can decolorize and biodegrade the organic load in the effluent at a faster time and can be used further to develop a continuous process of the treatment of textile effluents containing a wide variety of textile dyes Including, reactive, acid, direct dyes and vat dyes . as well as Textile auxiliaries.

## MATERIALS AND METHODS

### Collection of Effluent Samples

The effluent samples were collected from the treatment plants located at various common effluent treatment plants located in the areas of Karur, Tiruppur, and Coimbatore districts Tamil Nadu, South India. The effluent samples were pooled together and

used for the isolation of microbial strains and treatment trials.

#### Isolation, screening and Identification of Indigenous adapted bacterial and fungal strains from textile effluents

The microbial source (pooled effluent sample) was enriched in culture media for bacteria and for fungi as cited in Eltaief Khelifi *et al.*, 2008., The enriched Indigo carmine. About 1mg of dye was incorporated in 100 ml of Nutrient broth (bacteria) and potato dextrose broth (fungi) separately with each isolate and the decolorization was studied for these three dyes by measuring the optical density of the sample in a UV-Visible spectrophotometer (Eltaief Khelifi *et al.*, 2008). The efficient isolates of bacteria and fungi were selected and identified based on colony morphology, standard biochemical and Microbiological tests (Cappuccino and Sherman, 1999; Rafi *et al.*, 2002; Klich, 2002).

#### Physic-Chemical characterization of pooled untreated effluent

Various physical and chemical parameters (Chemical Oxygen Demand [COD], Total Hardness, Total Solids (TS), Total Dissolved Solids (TDS), Total suspended solids (TSS), Color, Turbidity and pH) were assessed for the pooled untreated effluent by standard methods (APHA, 1992).

#### Design of microbial consortia and Treatment trials

Each bacterial isolates were given a number and the fungal isolates were designated with an alphabet (Bacillus sp., - 1; Pseudomonas sp., - 2; Alcaligenes sp., 3; Aspergillus sp., - A; Penicillium sp., - B). Accordingly, A1, A2, A3, A12, A13, A23, A123, B1, B2, B3, B12, B13, B23, AB, AB1, AB2, AB3, AB12, AB13, AB23, AB123 are the 23 different combinations which were used for treatment trials. An initial inoculum concentration of 5%, of 23 different combinations of bacteria and fungi were inoculated to 200 ml of the textile effluent sample in a 250 ml Erlenmeyer flask and were incubated at room temperature in a metabolic shaker at 120 rpm for a period of 7 days. (Muhammed Asgher *et al.*, 2007)

#### Analytical procedures: Biodegradation and Biodecolorization assays

Various physical and chemical parameters of the effluent samples (COD, Hardness, TS, TDS, TSS, Color, Turbidity and pH) were studied from the first day onwards for a period of 7 days for all the different combinations of organisms used (APHA, 1989). The color intensity and the turbidity of the effluent sample

culture was then serially diluted and plated in the respective solid media. Those colonies on the isolation plates which were morphologically distinct and predominant were selected and screened were studied for their decolorization pattern on the three commonly used tough dyes Red BSID, Re yellow merl and were measured at 490 nm and 620 nm respectively (Amar *et al.*, 2010). Reduction of these parameters were assayed by the % of reduction on comparison with the untreated effluent using formula 1

$$A=100(A_i-A_t)/A_i \quad (1)$$

Where A is the Percentage of reduction of that particular parameter,  $A_i$  the initial concentration of the particular parameter and  $A_t$ , the concentration after specified time of the same parameter (Eltaief Khelifi *et al.*, 2008).

## RESULTS AND DISCUSSION

#### Isolation, Screening and Identification of Indigenous adapted bacterial and fungal strains from textile effluents

About 265 and 35 morphologically distinct bacterial and fungal isolates were obtained through dilution plating of textile effluents. 12 organisms (7 bacteria and 5 fungi) which showed decolorization on all the three dyes were selected and further screened. Among these, 5 organisms (2 fungus and 3 bacteria) capable of reducing all the three dyes, by more than 75% were found to be the efficient decolorizers. The selected bacterial isolates were identified as *Bacillus* sp., *Pseudomonas* sp., and *Alcaligenes* sp., and the results were given in the **Table 1** (Cappuccino and Sherman, 1999).

**Table 1:** Identification of the Isolated Bacterial Isolates by Microscopic and Biochemical Tests  
C-Cocci; R- Rod; A – Acid production; 1- 3 Isolates;

Isolates	1	2	3
Gram Stain	-	-	-
Shape	R	R	R
Indole	-	-	-
MR	-	-	-
VP	+	-	-
Citrate	-	+	-
Dextrose	A	-	-
Lactose	-	-	-
Mannitol	-	-	-
Sucrose	A	-	-
H2S	-	-	-
Urease	-	-	-

Catalase	-	+	+
Oxidase	+	+	+

The two efficient fungal strains were identified as *Aspergillus* sp., and *Penicillium* sp., based on their microscopic observation. The first strain showed a septate and dichotomous hyphae, at 45° angle branching. Conidial heads are radiate to loosely columnar. Conidiophores are coarsely roughened, uncolored, vesicles spherical, metulae covering nearly the entire vesicle in biseriate species. Conidial heads radiate, uni- and biseriate; however, some isolates may remain uniseriate, producing only phialides covering the vesicle which are the characteristic features of *Aspergillus* sp., (Klich, 2002). For the second fungus the hyphae were terverticillate and the conidia were spherical to elliptical in shape. Conidia were smooth and had a green color reflection in the mass. These microscopic features were found to be that of *Penicillium* sp., (Rafi and Sajjid, 2002)

### Physico-Chemical characterization of pooled untreated effluent

The initial values of the estimated parameters for the pooled untreated effluent sample and that of the permissible limits for the safety release of the effluents in the natural water body has been provided in Table 2.

**Table 2:** Physic-chemical characterization of pooled untreated effluent

Parameters	Pollution Control Norms	Initial values
Hardness (mg/l)	Not objectionable	325.125
COD (mg/l)	400 mg/l <	1819.13
TS (g/l)	50 mg/l	33.53
TSS (g/l)	3000 mg/l <	12.1
TDS	3000 mg/l <	21.43
pH	5-9	10.5
Color	Nil	1.096
Turbidity	Not objectionable	0.976

The organic content in the effluent sample was found to be very high. The color of the sample also was found unacceptable to be discharged in to the natural water body.

### Treatment trials using microbial consortia

Samples were withdrawn at an interval of every 24 hours and all the physico-chemical parameters were recorded for all the different combinations. A pattern of reduction in parameters was observed in all the combinations, which showed a continuous reduction from the first day and a maximum reduction was observed at the end of 5 days of incubation and the

parameters are given in table 3. There is no change in the pH in the treatment trials and this parameter is negligible since it remained well under the permissible limits. A maximum of 75% reduction in the COD was observed in the combination B23. The capability of combination to reduce COD increased from day 1 to 5 and a further increase in this COD was observed after 5 days. The increase in the COD value on the later days might be the evidence of inappropriate mixing ratio between microbial combinations and organic materials. About 5 different combinations (A3, B1, B13, B23, AB) gave more than 50 % reduction in COD after 120 hours of incubation. According to Sangyong *et al.*, a 90% reduction was obtained by using a combined biological, physical and chemical method. The total organic content removal in case of combined electrochemical and activated carbon absorption for waste water treatment was about 59% (Rajkumar *et al.*, 2005), but in the present study consortium was able to reduce the organic content of up to 75%. A maximum of 66 % reduction in TDS was observed for the combination A1.

**Table 3:** Percentage of reduction of the observed parameters after 5 days of incubation

Combinations	COD	Hardness	Color	TS	TSS	TDS	pH	Turbidity
A1	46.4	43.8	52.9	89.3	21.4	66.7	11.3	39.0
A2	25.0	28.6	36.8	73.1	14.3	50.0	13.6	37.9
A3	50.0	21.4	50.1	65.4	55.6	57.5	12.3	45.3
A12	12.5	31.3	54.8	87.5	30.0	61.4	13.6	35.0
A13	40.0	21.4	66.4	75.0	28.6	59.5	15.7	45.1
A23	12.5	28.6	53.0	90.0	37.5	69.0	13.6	44.2
A123	20.5	21.4	48.2	89.3	21.4	63.2	13.4	33.3
I23	16.7	26.7	37.4	78.6	14.3	55.0	13.6	51.9
B1	71.4	50.0	5.4	11.0	7.7	11.5	5.9	21.6
B2	33.3	14.3	21.4	24.3	15.4	25.5	5.1	17.2
B3	46.7	50.0	2.4	26.1	33.3	25.8	2.1	10.4
B12	28.6	38.5	12.7	48.1	50.0	48.0	0.7	6.6
B13	50.0	33.3	1.4	24.3	45.5	15.3	7.8	16.7
B23	75.0	50.0	6.2	54.7	70.4	54.0	11.4	5.8
B123	10.4	28.6	1.7	50.5	58.3	50.0	7.3	5.6
AB	71.4	21.4	1.5	51.8	84.6	51.6	7.4	5.4
AB1	33.3	33.3	3.3	12.2	6.0	10.0	3.9	18.9
AB2	15.9	35.7	8.7	32.5	55.7	10.1	5.8	22.9
AB3	8.3	30.8	7.2	24.5	16.4	11.2	3.1	56.9
AB12	15.3	25.0	17.2	5.0	26.9	9.5	4.9	30.8
AB13	33.3	30.8	7.7	28.2	40.0	10.7	5.8	36.0
AB23	18.8	9.1	3.0	29.6	20.6	14.4	3.1	38.2
AB123	9.4	25.0	3.8	23.2	54.1	12.6	9.5	35.3

More number of combinations of microbes was found to be efficient in the reduction of TDS than other parameters. There is also about 56% of reduction in the turbidity of the sample by the combination AB3 which showed that there is a clear reduction in the percentage of the suspended solids in this combination. The combinations B1, B3 and B23 were able to reduce the calcium and magnesium content of the pooled effluent up to 50 %. The combination A13 was able to efficiently decolorize the effluent sample up to 66.4%, apart from this there were 4 different combinations of microbes which were able to

decolorize the pooled effluent of more than 50% (A1, A3, A12 and A23). The reason for the other combinations of microbes that are not so efficient might be because of the incompatible nature of the microbes used in the combination or because of the action the secondary metabolites produced by one on the other. Decolorization time taken by the cultures to achieve 66% decolorization compares favorably with reports on dye decolorization by most of the white rot fungi which require 7–20 days period for 90% decolorization of a diverse range of synthetic dyes (Kirby *et al.*, 2000) and other mixed microbial cultures (Senan and Abraham 2004; Adedayo *et al.*, 2004). Microbial components of mixed microbial cultures are capable of decolorizing dyes via biotransformation and biodegradation (Banat *et al.*, 1994). The efficiency of the decolorization process depends on the survival, adaptability and activities of enzymes produced by microorganisms present in the mixed cultures (Cripps *et al.*, 1990; Senan and Abraham 2004). Normally the dye concentration in the effluent varies within a narrow range of 0.1–0.2 g/l (O'Neill *et al.*, 1999).

## SUMMARY

The combinations A1 and A12 were found to be the most efficient as they have efficiently reduced all the parameters under study than other combinations. There were a few other combinations which were efficient on a few particular parameters. These two combinations could be made use of in treatment trials in the industries.

## 5. CONCLUSION

Bacteria offers a cheaper and environment friendlier alternative for color removal in textile effluents. Biological treatment has been effective in reducing dye house effluents and when used properly has a lower operating cost than other remediation process. Decolorization of Azo dyes during biological effluent treatment can involve both adsorption to cell biomass and degradation by azo-bond reduction during anaerobic digestion. Degradation is expected to form aromatic amines, which may be toxic and recalcitrant to anaerobic treatment but degradable aerobically. Methods for the quantitative detection of substituted aromatic amines arising from azo-dye cleavage are complex.

Microbial consortium has become a very good source for the textile industry in getting rid of their effluent problem by Biodegradation and Decolorization process. Since they are cost effective and efficient it is highly recommended for the industries in making use of the consortium for the proper disposal of textile effluents.

The process has many advantages of which:

- The treatment uses no chemicals.
- The consortium disposes no harmful matters into the environment.
- The process eliminates chemical processing and vapor.
- No energy used and consequently zero carbon process. Also worth carbon credit.
- No complicated plants needed and less capital investment.

## ACKNOWLEDGEMENT

The authors thank The Department of Biotechnology, Ministry of Science & Technology, Government of India, INDIA, for their financial assistance and Dr. Osama Abdelwahab Rayis, Director, Africa City of Technology, SUDAN for his support.

## REFERENCES

- Adedayo, O, Javadpour S, Taylor C, Anderson WA, M Young M (2004). Decolorization and detoxification of methyl red by aerobic bacteria from a wastewater treatment plant. *World J Microbiol Biotechnol* 20:545–550
- Amar. A, Telke, Swati M. Joshi, Sheetal U. Jadhav, Dhawal P. Thamboli, Sanjay P. Goivindwar (2010). Decolorization and detoxification of Congo red and textile industry effluent by an isolated bacterium *Pseudomonas* sp. SU-EBT, *Biodegradation*, 21:283–296
- APHA, (1992). Standard methods for examination of water and wastewater APHA, AWWA, AWWA WPCF, Washington, DC.
- Banat, I. M., Nigam. P, Singh. D, and Marchant. R. (1996) "Microbial Decolorization of Textile Dye Containing Effluents: A Review," *Bioresour. Technol.*, 58, 217.
- Cappuccino, J.G. and N. Sherman (1999). *Microbiology: A Laboratory Manual*, 4th Ed., pp: 199–204. Addison Wesley Longman, Inc. Harlow, England
- Cripps C, Bumps JS, Aust SD (1990) Biodegradation of azo and heterocyclic dyes by *Phanerochaete chrysosporium*. *Appl Environ Microbiol* 58:3605–3613
- Eltaief Khelifi, Hassib, Bouallagui, Youssef Touhami, Jean-Jacques Godon, and Moktar Hamdi (2008), "Enhancement of textile wastewater decolorization and biodegradation by isolated bacterial and fungal strains", *Desalination and water treatment*. 2. 310-316.
- ISPCH (1995). *Industrial safety and pollution control handbook.*, A joint publication of National Safety Council and Associate (Data) Publishers Pvt. Ltd., Hyderabad, 2nd edition, 2nd reprint, pp. 451-466.
- Kirby N, Marchant R, McMullan G (2000). Decolorization of synthetic textile dyes by *Phlebia tremellosa*. *FEMS Microbiol Lett* 188:93–96
- Klich M. A. (2002). *Identification of common Aspergillus sp.*, 1st ed. Centraalbureau voor Schimmelcultures, Utrecht, Netherlands, 116pp.

- Muhammed Asgher, H. N. Bhatti, S. A. H. Shah, M. Javaid Asad and R. L. Legge (2007), "Decolorization potential of mixed microbial consortia for reactive and disperse textile dyestuffs", *Biodegradation*. 18:311-316.
- Murugalatha N., Mohankumar A., Sankaravadiyoo A. and Rajesh C. (2010) Textile effluent treatment by *Bacillus* species isolated from processed food, *African Journal of Microbiology Research* Vol. 4(20) pp. 2122-2126, 18 October,
- O'Neill C, Hawkes FR, Hawkes DL, Lourenco ND, Pinheiro HM, Delee W (1999) Color in textile effluents: sources, measurement, discharge consents and simulation: a review. *J Chem Technol Biotechnol* 74:1009–1018
- Rafi, M. and Sajjad-Ur-Rahman (2002). Isolation and Identification of Indigenous *Penicillium chrysogenum* Series. *Int. J. Agri. Biol.*, Vol. 4, No. 4.
- Rajkumar D, Palanivelu K, and Balasubramanian N,(2005). *J. Environ. Eng. Sci.* 4: 1–9.
- Senan RC, Abraham TE (2004) Bioremediation of textile azo dyes by aerobic bacterial consortium. *Biodegradation* 15:275–280.